Sample Tag





Tag must have attaching hole reinforced and the Attaching device must be non-reusable, attachable by hand, self-locking and non-releasable with a minimum unlocking strength of 50 pounds. (Like a non-reusable all-weather nylon cable tie.)

Both sides of tags must have DANGER in large Letters

INSTRUCTIONS DO NOT REMOVE THIS LOCK OR TAG AND DO NOT TURN ON ENERGY ISOLATING DEVICE.

REASON: DANGER TO PERSONNEL.

AUTHORIZED PER	RSON	SHOP/CODE
PHONE	DATE APPLIED _	TIME APPLIED
SUPERVISOR		AG CONTROL#
REASON FOR TA	AG	

Instructions **must include at least one** of the Following statements;

- DO NOT START
- DO NOT ENERGIZE
- DO NOT OPERATE
- DO NOT OPEN
- DO NOT CLOSE

Tag **must include** the following identifying Information:

- Equipment / Circuit affected
- Name of authorized person.
- Cognizant Shop or Code
- Work phone number of authorized person
- Name of authorized person's Supervisor
- Date and time tag / lock is applied
- # of Total # of tags if more than one is needed.
- Other information may be included on tag for purposes of documenting / tracking / logging of locks / tags.

Note: If you cannot locate tags that meet the required criteria, many of the sign making companies will make tags to your specifications, or you can order a rubber stamp which would imprint the required fields, in permanent ink, on a generic tag which you can order.